

OLINEIAL	
Credential Support	Bluetooth (BLE), Fingerprint, RFID Card, Face and PIN
IP Rating	Yes (IP65 Design)
	Proximity (EM Prox, HID Prox) and
RF Option	Smart Cards (Mifare, NFC Tag and HID iCLASS)
	(COSEC CPM Module Required)
CAPACITY	
Max. Users	50,000
Max. Template Storage	9,600 in 1: N Mode and 100,000 in 1:1 Mode

Max. Users	50,000
Max. Template Storage	9,600 in 1: N Mode and 100,000 in 1:1 Mode
Event Buffer	500,000
Templates per User	Up to 10 (Single Template per Finger Mode) Up to 5 (Dual Template per Finger Mode)
Cards per User	Up to 2

COMMUNICATION

GENERAL

Wi-Fi		
WLAN (802.11 b/g/n)		
Bluetooth (BLE 4.0)		
FCC ID		
Ethernet		
PoE		
RS-232		
Mobile Broadband		
Wiegand		
USB		

Yes (802.3 af) Frequency: 2.4 GHz, Frequency Range: 2412 MHz to 2485 MHz Frequency: 2.4 GHz, Frequency Range: 2402 MHz to 2480 MHz Z64-WL1835COM Yes (10/100 Mbps) Yes (IEEE 802.3 af) Yes Yes Wiegand IN, Wiegand OUT Available 1 USB Port (Data Transfer and 2G-3G Dongle)

INTERFACE

Exit Switch	Yes, RFID Card and PIN	
Door Status Sense	Programmable NO, NC, Supervised	
Door Lock Relay	30V DC @ 1 A, Form C, SPDT Relay	
Door Lock Power	Internal 12V DC @ 0.5A or External	

Aux-In	Programmable NO, NC, Supervised	
Aux-Out	30V DC @ 1 A, Form C, SPDT Relay	
Reader Interface Types	RS-232, and Wiegand IN/OUT	
Micro SD Card	Yes (Inbuilt 16 GB)	

HARDWARE

CPU	800 MHz ARM Cortex A8 Based Processor
Memory	256 MB Flash + 512 MB DDR3 RAM
Display	3.5" TFT Display with Capacitive Touch Panel
Display Size	320mm x 240mm
Buzzer	Yes
Operating Temperature	0 to +50 (32°F to 122°F)
Humidity	5% to 95% RH Non - Condensing
Tamper Detection	Yes
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from COSEC VEGA FAX)
	30V DC @1 A (Power to lock from External Adaptor)
Dimensions (W x H x D)	91mm x 186mm x 38mm (3.58"x7.32"x1.49")
Weight	0.54 Kgs (1.19 lbs.)

CERTIFICATES

CE, IEC, FCC, BIS, ROHS, IP65, Shock and Vibration Proof

COMPATIBILITY

System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA Server
	Panel Door with COSEC PANEL LITE V2

SENSOR

Sensor Name	Suprema Sensor
Sensor Technology	Optical Sensing
Encryption	256-bit AES
Waterproof	Yes
False Acceptance Ratio (FAR)	0.001%
False Rejection Ratio (FRR)	0.01%
Equal Error rate (ERR)	< 0.1%
Resolution (dpi)	500 dpi
Sensing Area	15.9mm x 17.9mm
Template Size	384 Bytes
Image Size (Pixel)	288mm x 288mm

APPLICATIONS

Access Control Time-Attendance Visitor Management Contract Workers' Management

Cafeteria Management Job Processing and Costing

*Due to continuous technology upgradations, product specifications are subject to change without notice.

ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology-driven and customer-focused organization, is committed to keeping pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.



MATRIX COMSEC Head Office 394-GIDC, Makarpura, Vadodara-390 010, India. Ph: (+91) 265-613-7222 E-mail: Inquiry@MatrixComSec.com

Factory 19-GIDC, Waghodia, Dist. Vadodara-391 760, India. Ph: (+91) 265-613-7222

MATRIX COMSEC - North America 2 Wickstead Crt, Brampton, Ontario, L6R 1N8. +1 408-643-0581 (USA) +1 437-266-1005 (Canada)

www.MatrixAccessControl.com